

Midwest Construction Products

GF9



Midwest Construction Products GF9 is a woven slit-tape geotextile made of 100% polypropylene. Midwest Construction Products' GeoForce line of Geotextiles are designed for superior performance and cost effective filtration, separation, drainage, reinforcement and erosion control. **GeoForce 9** resists ultraviolet deterioration, rotting, biological degradation, naturally encountered basics and acids. Polypropylene is stable within a pH range of 2 to 13. **GF9** conforms to the physical values listed below:

<i>PROPERTY</i>	<i>TEST PROCEDURE</i>	<i>METRIC</i>		<i>ENGLISH</i>	
		MARV		MARV	
Grab Tensile Strength	ASTM D-4632	1780	N	400	lbs
Grab Elongation	ASTM D-4632	20 / 15	%	20 / 15	%
Wide Width Tensile	ASTM D-4595	58.4	kN/m	4000	Lb/ft.
Trapezoid Tear	ASTM D-4533	667.5	N	150	lbs
Puncture	ASTM D-4833	801	N	180	lbs
Permittivity	ASTM D-4491	0.062	sec ⁻¹	0.062	sec ⁻¹
UV Resistance (500 hrs)	ASTM D-4355	80	%	80	%
Water Flow Rate	ASTM D-4491	366.7	lpm/m ²	9	gpm/ft ²

*At the time of manufacturing. Handling, storage, and shipping may change these properties.

PACKAGING	
Roll Dimension (W x L) - Ft	15x300
Square Yards per Roll	500
Estimated Roll Weight - lbs	280

* At the time of manufacturing. Handling may change these properties.

This information is provided for reference purposes only and is not intended as a warranty or guarantee. Midwest Construction Products assumes no liability in connection with the use of this information.

For further information please call 800-532-2381