

# Midwest Construction Products

## GF2



**Midwest Construction Products GF2** is a woven slit-tape geotextile made of 100% polypropylene. Midwest Construction Products' GeoForce line of Geotextiles are designed for superior performance and cost effective filtration, separation, drainage, reinforcement and erosion control. **GeoForce 2** resists ultraviolet deterioration, rotting, biological degradation, naturally encountered basics and acids. Polypropylene is stable within a pH range of 2 to 13. **GF2** conforms to the physical values listed below:

<i>PROPERTY</i>	<i>TEST PROCEDURE</i>	<i>METRIC</i>		<i>ENGLISH</i>	
		MARV		MARV	
Grab Tensile Strength (W/F)	ASTM D-4632	668 / 445	N	150 / 100	lbs
Grab Elongation	ASTM D-4632	20/15	%	20/15	%
Trapezoid Tear	ASTM D-4533	178	N	40	lbs
Puncture	ASTM D-4833	267	N	60	lbs
Permittivity	ASTM D-4491	0.080	sec <sup>-1</sup>	0.080	sec <sup>-1</sup>
A.O.S.	ASTM D-4751	0.6	mm	30	U.S. Sieve
UV Resistance (500 hrs)	ASTM D-4355	80	%	80	%
Water Flow Rate	ASTM D-4491	228	lpm/m <sup>2</sup>	5.6	gpm/ft <sup>2</sup>

\*At the time of manufacturing. Handling, storage, and shipping may change these properties.

<b>PACKAGING</b>	
<b>Roll Dimension (W x L) - Ft</b>	12.5x504 / 15x420 / 17.5x360
<b>Square Yards per Roll</b>	700
<b>Estimated Roll Weight - lbs</b>	150

\* At the time of manufacturing. Handling may change these properties.

This information is provided for reference purposes only and is not intended as a warranty or guarantee. Midwest Construction Products assumes no liability in connection with the use of this information.